


EARTHING AND SHORT CIRCUITING CABLES AND BARE WIRES

Copper wire braidings, flat

Bare copper braidings, flat



TECHNICAL DATA



Standard
TP PRAKAB 11/02

DESIGN



Nominal cross-section (mm ²)	Single wire diameter (mm)	Max. conductor resistance (Ω/km)	Width of flattened conductor (mm)	Height of flattened conductor (mm)	Total weight appr. (kg/km)
6	0.071	3.248	8.5	0.9	55
10	0.071	1.949	11.5	1.2	95
10	0.1	1.949	11.2	1.3	99
16	0.071	1.218	15.2	1.4	145
16	0.1	1.218	15.5	1.5	155
20	0.071	0.974	16.8	1.7	195
25	0.071	0.78	19	1.9	245
25	0.1	0.78	20	2	250
25	0.2	0.78	22	1.6	218
35	0.071	0.557	21.5	2.4	365
35	0.1	0.557	24	2.2	335
35	0.2	0.557	24.5	2.4	345
50	0.1	0.39	28.5	2.8	525
50	0.2	0.39	31	2.7	500
70	0.2	0.278	35	3.8	700

CONTACT PERSON

Jan Pietron
Key Account Manager
+420 604 471 907
jan.pietron@koneka.cz

