



We Make Modern
Life Possible

TELECOMMUNICATIONS CABLES

BM-YY

PVC Fire alarm cable, unscreened



TECHNICAL DATA



Standard

EN 50575 in Anlehnung an ÖVE-K 35



Test Voltage

800 Veff



Rated Voltage

max. 300 Vss



Bending radius (min.)

7,5 x Ø der Leitung



Fire properties

EN 60332-1-2: selbstverlöschend CPR-Klassifizierung: Eca



Core identification

coloured according to ÖVE-K 35



Temperature range

Laying temperature: min. -5°C
Fixed installation: -30°C up to 70°C
Flexible use: -5°C up to 50°C

DESIGN



1 Kupferleiter, rund eindrätig

2 Aderisolation (PVC)

3 Mantel (PVC rot mit Aufdruck „Brandmeldeleitung“)

Electrical parameters

Conductor diameter	mm	0.8
Conductor resistance, max. at 20 °C	Ω/km	36.6
Insulation resistance, min. at 20 °C	MΩ/km	100

Number of cores x conductor diameter	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
2 x 0.8	4.5	30	100 R, 500 Sp, 1000 Sp
3 x 0.8	4.8	36	100 R, 500 Sp, 1000 Sp
4 x 0.8	5.5	44	100 R, 500 Sp, 1000 Sp

CONTACT PERSON

Dogan Özcan
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

