



We Make Modern
Life Possible

HALOGEN-FREE TELECOMMUNICATION, FIRE SIGNALING AND ELECTRONIC
CABLES

JB-H(St)H...Bd

Fire alarm cable, halogen-free, screened



TECHNICAL DATA



Standard
adapted to DIN VDE 0815



Test Voltage
800 Veff (core/screen)



Rated Voltage
max. 300 V



Bending radius (min.)
7,5 x Ø der Leitung



Fire properties
EN 61034-2: low smoke emission



Core identification
DIN VDE 0815



Temperature range
Laying temperature: min. -5°C
Fixed installation: -30°C up to 70°C
Flexible use: -5°C up to 50°C

DESIGN



Electrical parameters

Conductor diameter	mm	0.8
Loop resistance max	Ω/km	73.2
Insulation resistance, min. at 20 °C	MΩ/km	100
Mutual capacitance (approx. value), at 800 Hz	nF/km	144
Mutual capacitance, max.	nF/km	120
Capacitance unbalance k9 (pairs), max. at 800 Hz (80 % values)	pF/km	200
Capacitance unbalance k9 (pairs), max. at 800 Hz (100 % of values)	pF/km	300

Number of pairs x nominal diameter	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
1 x 2 x 0.8	5.4	37	500 T, 1000 T
2 x 2 x 0.8	5.9	52	500 T, 1000 T
4 x 2 x 0.8	11.0	152	500 T, 1000 T
6 x 2 x 0.8	11.5	152	500 T, 1000 T
10 x 2 x 0.8	13.5	214	500 T, 1000 T
20 x 2 x 0.8	16.0	336	500 T, 1000 T
30 x 2 x 0.8	19.5	490	500 T, 1000 T
40 x 2 x 0.8	22.0	625	500 T, 1000 T
50 x 2 x 0.8	25.0	788	500 T, 1000 T
60 x 2 x 0.8	27.0	924	500 T, 1000 T
80 x 2 x 0.8	30.5	1218	500 T, 1000 T
100 x 2 x 0.8	34.0	1500	500 T, 1000 T

CONTACT PERSON

Dogan Özcan
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

