



We Make Modern
Life Possible

ALUMINIUM - VDE

NA2XS(F)2Yv 6/10 kV

XLPE/HDPE medium voltage underground
cable, longitudinally water-proof



TECHNICAL DATA



Standard
DIN VDE 0276-620



Certificate
VDE Germany



Test Voltage
18 kV



Rated Voltage
6/10 kV (U₀/U)




Bending radius (min.)
15 x Ø of cable



Temperature range
Laying temperature: min. -20°C
Operating temperature: -50°C up to 90°C
Conductor temperature: max. 90°C
Short circuit temperature: max. 250°C

DESIGN



Number of cores x nominal cross-section / cross-section of screen (mm ²)	Mutual capacitance (nF/ km)	Max. conductor resistance (Ω/ km)	Current rating in the earth (A)	Current rating in the air (A)	Standard length- s/packing (m)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
1 x 35 RM / 16	0.24	0.868	145	153	500 T, 1000 T	28.0	650
1 x 50 RM / 16	0.26	0.641	171	183	500 T, 1000 T	27.0	750
1 x 70 RM / 16	0.3	0.443	208	228	500 T, 1000 T	28.0	850
1 x 95 RM / 16	0.31	0.32	248	278	500 T, 1000 T	30.0	950
1 x 120 RM / 16	0.34	0.253	325	285	500 T, 1000 T	32.0	1100
1 x 150 RM / 25	0.39	0.206	315	364	500 T, 1000 T	32.0	1150
1 x 185 RM / 25	0.42	0.164	357	418	500 T, 1000 T	36.0	1450
1 x 240 RM / 25	0.47	0.125	413	494	500 T, 1000 T	38.0	1600
1 x 300 RM / 25	0.51	0.1	466	567	500 T, 1000 T	47.5	2100
1 x 400 RM / 35	0.57	0.078	529	660	500 T, 1000 T	43.0	2350
1 x 500 RM / 35	0.63	0.061	602	767	500 T, 1000 T	55.0	2850
1 x 630 RM / 35	0.65	0.047	675	890	500 T, 1000 T	52.0	3060

CONTACT PERSON

Dogan Özcan
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

