



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® CHAIN C

PVC/PVC drag chain cable, screened



TECHNICAL DATA



Standard
Based on VDE 0285



Test Voltage
4000 V / 50 Hz



Rated Voltage
300/500 V (U₀/U)



Bending cycles
3 million



Bending radius (min.)
Fixed installation: $7.5 \times \varnothing$ of cable
Flexible use: $10 \times \varnothing$ of cable



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant



Core identification
Black (continuously numbered), from 3 cores with green/yellow ground conductor



Temperature range
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



- 1 Bare copper conductors, super fine wires class 6 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Core insulation of special compound based on polyvinyl chloride (PVC)
- 3 Cores stranded in layers with short lay-lengths
- 4 Non-woven wrapping over each stranding layer
- 5 Inner sheath of special compound based on polyvinyl chloride (PVC)
- 6 Tinned copper wire braiding
- 7 Non-woven tape separation over braiding (optional)
- 8 Outer sheath of special compound based on polyvinyl chloride (PVC), colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 0.5	6.9	73
3 G 0.5	7.3	84
4 G 0.5	7.9	98
5 G 0.5	8.6	110
7 G 0.5	9.8	141
12 G 0.5	11.5	201
18 G 0.5	13.4	285
25 G 0.5	15.9	394
2 x 0.75	7.3	85
3 G 0.75	7.8	98
4 G 0.75	8.4	116
5 G 0.75	9.0	128
7 G 0.75	10.7	178
12 G 0.75	12.5	253
18 G 0.75	14.9	367
25 G 0.75	17.4	496
2 x 1	7.7	97
3 G 1	8.2	116
4 G 1	8.9	134
5 G 1	9.8	154
7 G 1	11.4	207
12 G 1	13.4	314
18 G 1	16.1	443
25 G 1	18.8	612
2 x 1.5	8.4	117
3 G 1.5	9.0	139
4 G 1.5	9.9	169
5 G 1.5	10.9	201
7 G 1.5	12.7	262
12 G 1.5	15.2	404
18 G 1.5	17.8	560
25 G 1.5	21.2	788
3 G 2.5	11.0	206
4 G 2.5	11.9	244
5 G 2.5	13.2	306
7 G 2.5	15.8	418
12 G 2.5	20.4	690
18 G 2.5	24.0	994
25 G 2.5	28.2	1420
4 G 4	13.7	360
5 G 4	15.3	430
7 G 4	20.0	670
4 G 6	16.1	514
7 G 6	23.0	862



CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

