



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® SERVO C

PVC/PVC servo-motor supply cable, screened



TECHNICAL DATA



Test Voltage
4000 V / 50 Hz



Rated Voltage
0.6/1 kV (Uo/U)



Bending radius (min.)
Fixed installation: $7.5 \times \varnothing$ of cable
Flexible use: $20 \times \varnothing$ of cable



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant



Core identification
Supply cores: black (continuously numbered) with green/yellow ground conductor
Control pairs 0.34 mm²: colour coded
Control pairs from 0.75 mm²: black with white numbers



Temperature range
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



- 1 Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Core insulation of special compound based on polyvinyl chloride (PVC)
- 3 Control pairs individually screened with plastic laminated aluminium tape and tinned copper wires
- 4 Cores are stranded together with optimal lay-length
- 5 Plastic tape
- 6 Tinned copper wire braiding
- 7 Non-woven tape separation over braiding (optional)
- 8 Outer sheath of special compound based on polyvinyl chloride (PVC), colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
4 G 0.75 + 2 x (2 x 0.34)	10.2	157
4 G 1.5 + 2 x (2 x 0.75)	13.2	274
4 G 2.5 + (2 x 2 x 0.75)	14.7	333
4 G 4 + (2 x 0.75 + 2 x 1)	16.2	424
4 G 6 + (2 x 0.75 + 2 x 1)	17.8	553
4 G 10 + (2 x 0.75 + 2 x 1)	21.6	815
4 G 16 + (2 x 2 x 1)	24.1	1088
4 G 25 + (2 x 2 x 1.5)	29.7	1665

CONTACT PERSON

Dogan Özcan, MSc
 Head of Technical Department
 +43 (0) 1 70170-154
 dogan.oezcan@skw.at

