



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® CHAIN

PVC/PVC drag chain cable, unscreened



TECHNICAL DATA



Standard
Based on VDE 0285



Test Voltage
4000 V / 50 Hz



Rated Voltage
300/500 V (U₀/U)



Bending cycles
3 million



Bending radius (min.)
Fixed installation: $7.5 \times \varnothing$ of cable
Flexible use: $10 \times \varnothing$ of cable



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant



Core identification
Black (continuously numbered), from 3 cores with green/yellow ground conductor



Temperature range
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



1 Bare copper conductors, super fine wires class 6 according to DIN EN 60228 / VDE 0295 / IEC 60228



2 Core insulation of special compound based on polyvinyl chloride (PVC)



3 Cores stranded together in short lay-lengths



4 Non-woven wrapping over each stranding layer



5 Outer sheath of special compound based on polyvinyl chloride (PVC), colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 0.5	5.2	32
3 G 0.5	5.5	41
4 G 0.5	6.1	52
5 G 0.5	6.6	64
7 G 0.5	8.0	92
12 G 0.5	9.6	128
18 G 0.5	11.5	195
25 G 0.5	14.2	284
2 x 0.75	5.7	39
3 G 0.75	6.2	51
4 G 0.75	6.8	65
5 G 0.75	7.4	80
7 G 0.75	8.9	117
12 G 0.75	10.5	169
18 G 0.75	12.7	254
25 G 0.75	15.8	376
2 x 1	6.0	46
3 G 1	6.6	60
4 G 1	7.3	78
5 G 1	7.9	96
7 G 1	9.6	144
12 G 1	11.4	205
18 G 1	13.9	314
25 G 1	17.6	498
2 x 1.5	6.7	60
3 G 1.5	7.4	80
4 G 1.5	8.1	102
5 G 1.5	9.1	130
7 G 1.5	10.8	192
12 G 1.5	13.0	273
18 G 1.5	15.6	417
25 G 1.5	19.8	632
3 G 2.5	9.0	128
4 G 2.5	10.0	161
5 G 2.5	11.2	205
7 G 2.5	13.5	300
12 G 2.5	16.0	440
18 G 2.5	20.4	703
25 G 2.5	24.7	1054
3 G 4	10.6	176
4 G 4	11.8	227
5 G 4	13.5	298
7 G 4	18.6	446
3 G 6	13.0	280



Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
4 G 6	14.2	358
7 G 6	19.8	614

CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

