



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® CHAIN 11

PVC/PUR drag chain cable, unscreened



TECHNICAL DATA



Standard
Based on VDE 0285



Test Voltage
4000 V / 50 Hz



Rated Voltage
300/500 V (U₀/U)



Bending cycles
5 million



Bending radius (min.)
Fixed installation: $7.5 \times \varnothing$ of cable
Flexible use: $10 \times \varnothing$ of cable



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant



Core identification
Black (continuously numbered), from 3 cores with green/yellow ground conductor



Temperature range
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



Bare copper conductors, super fine wires class 6 according to DIN EN 60228 / VDE 0295 / IEC 60228



Core insulation of special compound based on polyvinyl chloride (PVC)



Cores stranded in layers with short lay-lengths



Non-woven wrapping over each stranding layer



Special polyurethane (PUR) outer sheath, colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 0.5	5.3	31
3 G 0.5	5.7	39
4 G 0.5	6.3	51
5 G 0.5	6.7	62
7 G 0.5	8.0	90
12 G 0.5	9.6	125
18 G 0.5	11.5	191
25 G 0.5	14.2	280
2 x 0.75	5.7	38
3 G 0.75	6.2	50
4 G 0.75	6.8	64
5 G 0.75	7.4	78
7 G 0.75	8.9	115
12 G 0.75	10.5	166
18 G 0.75	12.7	249
25 G 0.75	15.6	356
2 x 1	6.0	44
3 G 1	6.6	59
4 G 1	7.3	76
5 G 1	7.9	94
7 G 1	9.6	141
12 G 1	11.4	201
18 G 1	13.9	310
25 G 1	17.4	490
34 G 1	18.4	776
41 G 1	19.7	925
50 G 1	21.7	1092
65 G 1	30.9	1400
2 x 1.5	6.7	59
3 G 1.5	7.4	78
4 G 1.5	8.1	100
5 G 1.5	9.1	128
7 G 1.5	10.8	189
12 G 1.5	13.0	269
18 G 1.5	15.6	415
25 G 1.5	19.4	628
34 G 1.5	20.6	1048
42 G 1.5	22.4	1290
50 G 1.5	24.2	1520
3 G 2.5	9.0	126
4 G 2.5	10.0	158
5 G 2.5	11.2	201
7 G 2.5	13.5	295
12 G 2.5	16.0	436



Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
18 G 2.5	20.4	696
25 G 2.5	24.7	1042
3 G 4	10.6	175
4 G 4	12.0	224
5 G 4	13.5	292
7 G 4	18.6	440
3 G 6	13.0	276
4 G 6	14.2	352
7 G 6	19.8	608
3 G 10	16.2	660
4 G 10	18.1	750
5 G 10	20.3	990
7 G 10	24.3	1300
4 G 16	21.1	1200
5 G 16	23.5	1500

CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

