



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® SPIRAL 11

PVC/PUR multicore control cable, coilable



TECHNICAL DATA



Test Voltage
4000 V / 50 Hz



Rated Voltage
300/500 V (Uo/U)



Core identification
Colour coded or continuously numbered according to internal standards or customer requirements



Temperature range
Operating temperature: -5°C up to 70°C

DESIGN



1

Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228

2

Core insulation of special compound based on polyvinyl chloride (PVC)

3

Cores are stranded in layers with optimal lay-length

4

Mineral powder separation

5

Special polyurethane (PUR) outer sheath, shiny finished, colour: grey (RAL 7001), other colours upon request

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 0.75	5.7	42
3 G 0.75	6.1	52
4 G 0.75	6.7	65
5 G 0.75	7.3	78
7 G 0.75	8.0	98
12 G 0.75	10.1	166
18 G 0.75	12.2	237
2 x 1	6.1	49
3 G 1	6.6	64
4 G 1	7.1	78
5 G 1	7.6	94
7 G 1	8.5	117
12 G 1	11.0	204
18 G 1	13.1	286
2 x 1.5	6.5	62
3 G 1.5	7.1	79
4 G 1.5	7.5	105
5 G 1.5	8.6	123
7 G 1.5	9.6	163
12 G 1.5	12.7	279
18 G 1.5	14.9	398
3 G 2.5	8.6	123
4 G 2.5	9.2	158
5 G 2.5	10.5	189

CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

