



We Make Modern
Life Possible

SOLAR CABLES

H1Z2Z2-K

Solar cable, halogen-free



TECHNICAL DATA



Standard

EN 50618
EN 50575:2014 + EN 50575/A1:2016



Rated Voltage

1/1.5 kV (U₀/U)



Test Voltage

6,5 kV / 50 Hz



Bending radius (min.)

4 x Ø of cable (fixed installed)
6 x Ø of cable (free motion)



Core identification

Grey



Fire properties

EN 60332-1-2: flame retardant
CPR classification: Eca



Temperature range

Laying temperature: min. -40°C
Operating temperature: -40°C up to 90°C
Conductor temperature: max. 90°C
Short circuit temperature: max. 200°C
Fixed installation: -40°C up to 120°C
Flexible use: -25°C up to 120°C

DESIGN



1

Tinned copper conductor, fine wire (-K)

2

Core insulation (cross-linked polyolefin copolymer)

3

Sheath (cross-linked polymer compound black, red or blue)

Nominal cross-section (mm²)	Max. conductor resistance (Ω/km)	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
15	13.7	5.0	30	500 SP, 1000 SP
25	8.21	5.4	43	500 SP, 1000 SP
4	5.09	6.6	58	500 SP, 1000 SP
6	3.39	7.4	79	500 SP, 1000 SP
10	1.95	8.8	128	500 SP, 1000 SP
16	1.24	10.1	185	500 D, 1000 D
25	0.795	12.5	277	500 D, 1000 D
35	0.565	14.0	369	500 D, 1000 D
50	0.393	16.3	557	500 D, 1000 D
70	0.277	18.7	767	500 D, 1000 D
95	0.21	20.8	912	500 D, 1000 D
120	0.164	24.2	1233	500 D, 1000 D
150	0.132	25.5	1540	500 D, 1000 D
185	0.108	28.5	1833	500 D, 1000 D
240	0.082	32.1	2450	500 D, 1000 D

CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

