



We Make Modern
Life Possible

PVC AND RUBBER CABLES AND WIRES

H05V-K (YSf)

PVC insulated wire, fine core



TECHNICAL DATA



Standard
EN 50525-2-31



Rated Voltage
300/500 V (U₀/U)



Test Voltage
2 kV



Bending radius (min.)
4 x Ø of wire



Core identification
HD 308 S2



Fire properties
EN 60332-1-2: flame retardant and self-extinguishing



Certificate
ÖVE Austria



Temperature range
Laying temperature: min. 5°C
Operating temperature: -30°C up to 70°C
Conductor temperature: max. 70°C
Short circuit temperature: max. 160°C

DESIGN



Copper conductor, fine wire (-K)



Core insulation (PVC)

Nominal cross-section (mm ²)	Core colours	Max. conductor resistance (Ω/km)	Outer diameter appr. (mm)	Total weight appr. (kg/ km)	Standard lengths/packi- ng (m)
0.5	bk, bn, bu, vt, rd, og, ye, gy, gn, wh, gnye	39.0	2.1	9	100 R
0.75	bk, bn, rd, bu, wh	26.0	2.2	12	100 R
1	bk, bn, bu, vt, rd, og, ye, gy, gn, wh, gnye	19.5	2.4	14	100 R

CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

