



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® CHAIN 911 UL/c(UL)

UL recognized PP/PUR drag chain cable,
unscreened



TECHNICAL DATA



Standard
Based on VDE 0285



Rated Voltage
300/500 V (U₀/U)
1000 V (UL/CSA)



Test Voltage
4000 V / 50 Hz



Bending radius (min.)
Fixed installation: 5 x ϕ of cable
Flexible use: 7.5 x ϕ of cable



Bending cycles
5 million



Core identification
Black (continuously numbered), from 3 cores
with green/yellow ground conductor



Fire properties
EN 60332-1-2: self-extinguishing and flame
retardant
UL: vertical flame test VW-1, cable flame test
CSA: FT1



Certificate
UL AWM Style 20234
CSA C22.2 No.210-11, AWM



Temperature range
Fixed installation: -50°C up to 80°C
Flexible use: -30°C up to 80°C

DESIGN



1

Bare copper conductors, super fine wires class 6 according
to DIN EN 60228 / VDE 0295 / IEC 60228

2

Core insulation of polypropylene compound (PP)

3

Cores stranded in layers with short lay-lengths

4

Non-woven wrapping over each stranding layer

5

Special polyurethane (PUR) outer sheath, colour: grey (RAL
7001)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 0.5	5.0	33
3 G 0.5	5.2	40
4 G 0.5	6.5	54
5 G 0.5	7.0	62
7 G 0.5	7.7	76
12 G 0.5	9.1	114
18 G 0.5	11.0	165
25 G 0.5	13.2	218
2 x 0.75	5.6	42
3 G 0.75	5.9	50
4 G 0.75	6.7	61
5 G 0.75	7.2	72
7 G 0.75	8.8	100
12 G 0.75	10.2	158
18 G 0.75	12.2	219
25 G 0.75	15.4	314
2 x 1	6.0	48
3 G 1	6.5	61
4 G 1	7.2	72
5 G 1	7.7	93
7 G 1	9.5	122
12 G 1	11.2	196
18 G 1	13.7	278
25 G 1	17.2	385
36 G 1	20.1	625
41 G 1	22.0	779
50 G 1	24.0	953
65 G 1	27.2	1205
2 x 1.5	6.7	68
3 G 1.5	7.3	83
4 G 1.5	7.9	102
5 G 1.5	9.0	128
7 G 1.5	10.6	177
12 G 1.5	12.5	275
18 G 1.5	15.2	405
25 G 1.5	19.0	562
36 G 1.5	22.2	880
42 G 1.5	24.0	1209
50 G 1.5	26.2	1449
3 G 2.5	8.8	122
4 G 2.5	9.8	163
5 G 2.5	11.0	196
7 G 2.5	13.3	268
12 G 2.5	15.8	446



Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
18 G 2.5	18.8	665
25 G 2.5	24.0	932
4 G 4	12.8	240
5 G 4	14.1	298
7 G 4	16.9	418
4 G 6	14.9	354
7 G 6	19.0	610
4 G 10	18.4	685
5 G 10	20.7	817
7 G 10	24.7	1023
4 G 16	21.3	1042
5 G 16	23.8	1292

CONTACT PERSON

Dogan Özcan, MSc
 Head of Technical Department
 +43 (0) 1 70170-154
 dogan.oezcan@skw.at

