



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® SERVO

PVC/PVC servo-motor supply cable,
unscreened



TECHNICAL DATA



Rated Voltage
0.6/1 kV (Uo/U)



Test Voltage
4000 V / 50 Hz



Bending radius (min.)
Fixed installation: $7.5 \times \varnothing$ of cable
Flexible use: $20 \times \varnothing$ of cable



Core identification
Supply cores: black (continuously numbered) with green/yellow ground conductor
Control pairs 0.34 mm²: colour coded
Control pairs from 0.75 mm²: black with white numbers



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant



Temperature range
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



- 1 Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Core insulation of special compound based on polyvinyl chloride (PVC)
- 3 Control pairs individually screened with plastic laminated aluminium tape and tinned copper wires. Aluminium tape is not applied for 1-pair versions
- 4 Cores are stranded together with optimal lay-length
- 5 Non-woven tape separation
- 6 Outer sheath of special compound based on polyvinyl chloride (PVC), colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
4 G 0.75 + 2 x (2 x 0.34)	9.6	133
4 G 1.5 + 2 x (2 x 0.75)	12.4	225
4 G 1.5 + (2 x 0.75)	11.6	184
5 G 1.5 + (2 x 0.75)	12.6	213
7 G 1.5 + (2 x 0.75)	12.8	251
5 G 2.5 + (2 x 0.75)	14.5	297
7 G 2.5 + (2 x 0.75)	15.5	373
4 G 2.5 + 2 x (2 x 0.75)	13.7	275
4 G 2.5 + (2 x 0.75)	13.2	246
4 G 4 + (2 x 0.75 + 2 x 1)	15.4	369
4 G 6 + (2 x 0.75 + 2 x 1)	16.6	458
4 G 10 + (2 x 0.75 + 2 x 1)	20.4	705
4 G 16 + (2 x 2 x 1)	23.2	976
4 G 25 + (2 x 2 x 1.5)	29.0	1524

CONTACT PERSON

Dogan Özcan, MSc
 Head of Technical Department
 +43 (0) 1 70170-154
 dogan.oezcan@skw.at

