



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® CHAIN SERVO 911 UL/c(UL)

UL recognized PP/PUR servo-motor supply
cable, halogen-free for drag chain application,
unscreened



TECHNICAL DATA



Rated Voltage
0.6/1 kV (Uo/U)
1000 V (UL/CSA)



Test Voltage
4000 V / 50 Hz



Bending radius (min.)
Fixed installation: $5 \times \phi$ of cable
Flexible use: $7.5 \times \phi$ of cable



Bending cycles
5 million



Core identification
Supply cores: black (continuously numbered)
with green/yellow ground conductor
control cores: black with white number printing



Fire properties
EN 60332-1-2: self-extinguishing and flame
retardant
UL: vertical flame test VW-1, cable flame test
CSA: FT1



Certificate
UL AWM Style 20234
CSA C22.2 No. 210-11, AWM



Temperature range
Fixed installation: -50°C up to 80°C
Flexible use: -30°C up to 80°C

DESIGN



1 Bare copper conductors, super fine wires class 6 according
to DIN EN 60228 / VDE 0295 / IEC 60228



2 Core insulation of special compound based on
polypropylene (PP)



3 Control pairs individually screened with plastic laminated
aluminium tape and tinned copper wires



4 Cores stranded together in short lay-lengths



5 Non-woven tape separation



6 Special polyurethane (PUR) outer sheath, colour: orange
(RAL 2003) or grey (RAL 7001)

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
4 G 1.5 + (2 x 1.5)	11.9	215
4 G 2.5 + (2 x 1.5)	13.1	268
4 G 4 + (2 x 1.5)	14.3	326
4 G 6 + (2 x 1.5)	16.2	410
4 G 10 + (2 x 1.5)	18.6	580
4 G 16 + (2 x 1.5)	22.5	887
4 G 1.5 + 2 x (2 x 0.75)	12.5	215
4 G 2.5 + 2 x (2 x 0.75)	14.3	306
4 G 2.5 + 2 x (2 x 1.0)	14.5	312
4 G 4 + (2 x 1) + (2 x 1.5)	15.8	392
4 G 6 + (2 x 1) + (2 x 1.5)	17.3	465

CONTACT PERSON

Dogan Özcan, MSc
 Head of Technical Department
 +43 (0) 1 70170-154
dogan.oezcan@skw.at

