



We Make Modern
Life Possible

INDUSTRIAL CABLES

FLEXICS® YSLYv-K35 400Hz 7x35+6x(4x1)

Ground power supply cable, with control
cores for fixed installation



TECHNICAL DATA



Rated Voltage
0.6/1 kV (U₀/U)



Test Voltage
4000 V / 50 Hz



Bending radius (min.)
5 x Ø of cable



Core identification
Central blue core, other cores black (continuously numbered)



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant



Temperature range
Fixed installation: -40°C up to 70°C
Flexible use: -15°C up to 70°C

DESIGN



1

Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228

2

Power supply control cores insulation of special cold resistant mixture of polyvinyl chloride (PVC); control cores of special compound based on polyvinyl chloride (PVC)

3

Power supply cores (black with No. 1-6) stranded over central core (blue) with 6 star-quads in the interstices

4

Non-woven tape separation

5

Outer sheath of special cold resistant compound based on polyvinyl chloride (PVC), colour: black (RAL 9005)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
7 x 35 + 6 x (4 x 1)	37.0	3109

CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

