



We Make Modern
Life Possible

POWER CABLES AND OVERHEAD LINES 0.6/1 kV

1-AYKY-OT

PVC/PVC hybrid energy cables, with polymeric
tube



TECHNICAL DATA



Standard
TP PRAKAB 02/08



Rated Voltage
0.6/1 kV



Test Voltage
core/core 4 kV / 50 Hz



Bending radius (min.)
15 x $\varnothing$ of cable



Core identification
ČSN 33 0166 ed. 2



Fire properties
EN 60332-1-2: flame retardant and self-extinguishing
CPR Classification: Eca




Certificate
EZÚ Czech Republic



Temperature range
Laying temperature: min. -5°C
Operating temperature: -50°C up to 70°C
Conductor temperature: max. 70°C

DESIGN



Optical cable (is not included power cable)



HDPE tube



Aluminium conductor, sector-shaped stranded (SM)



Core insulation (PVC)



Inner covering (Plastic tape)



Sheath (PVC black, UV-resistant)

Number of cores x nominal cross-section (mm²)	Max. conductor resistance (Ω/km)	Current rating in the earth (A)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
3 x 240 + 120 SM/SM + OT 12/8	0.125 / 0.253	364	338	56.5	3985

CONTACT PERSON

Dogan Özcan, MSc
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

