



We Make Modern
Life Possible

CONTROL AND ELECTRONIC CABLES

2XSL(St)CH-J 0.6/1 kV EMV

XLPE/FRNC motor power supply cable,
halogen-free, screened



TECHNICAL DATA



Standard
DIN VDE 0276-603



Test Voltage
4000 V / 50 Hz



Rated Voltage
0.6/1 kV (U₀/U)



Bending radius (min.)
Fixed installation: 7.5 x Ø of cable
Flexible use: 15 x Ø of cable



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant
EN 60332-3-24 (Category C): reduced flame propagation
EN 61034: smoke density
EN 60754: halogen-free
CPR classification: Dca



Core identification
HD 308 S2



Temperature range
Conductor temperature: max. 90°C
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



1

Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228

2

Core insulation of cross-linked polyethylene (XLPE)

3

Cores are stranded together with optimal lay-length

4

Plastic tape separation (optional)

5

Plastic bonded aluminium tape and tinned copper wire braiding

6

Outer sheath of special flame retardant non-corrosive compound (FRNC), colour: black (RAL 9005)

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
4 G 1.5	10.6	244
4 G 2.5	12.3	318
4 G 4	14.0	513
4 G 6	16.1	670
4 G 10	19.7	914
4 G 16	23.0	1367
4 G 25	27.3	1970
4 G 35	30.3	2763
4 G 50	35.0	3126
4 G 70	40.0	4182
4 G 95	45.0	5725

CONTACT PERSON

Dogan Özcan, MSc
 Head of Technical Department
 +43 (0) 1 70170-154
 dogan.oezcan@skw.at

