

MEDIUM VOLTAGE CABLES 10 – 30 kV

A2XS(F)2Y 18/30 kV IEC

XLPE/HDPE medium voltage underground
cable, longitudinally water-proof



TECHNICAL DATA



Standard
IEC 60502-2



Rated Voltage
18/30 kV (U_o/U)
36 kV (U_m)



Test Voltage
63 kV / 50 Hz



Bending radius (min.)
15 x Ø of cable



Fire properties
CPR Classification: Fca




Certificate
EZÚ Czech Republic



Temperature range
Laying temperature: min. -20°C
Operating temperature: -50°C up to 90°C
Conductor temperature: max. 90°C
Short circuit temperature: max. 250°C

DESIGN



- 1 Aluminium conductor, round stranded compacted (RMk)
- 2 Inner semi-conductive layer (conductive XLPE)
- 3 Insulation (XLPE)
- 4 Outer semi-conductive layer (conductive XLPE)
- 5 Tape (semi-conducting layer)
- 6 Metallic screen (copper wires with copper tape)
- 7 Swelling tape (longitudinal water tightness)
- 8 Sheath (HDPE black, UV-resistant)

Number of cores x nominal cross-section / cross-section of screen (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the earth (A)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
1 x 150 RM / 25	0.206	319	366	41.1	1551
1 x 185 RM / 25	0.164	361	420	42.4	1687
1 x 240 RM / 25	0.125	417	496	45.3	1964
1 x 300 RM / 25	0.1	471	569	47.5	2202
1 x 400 RM / 35	0.078	535	660	50.9	2703
1 x 500 RM / 35	0.061	609	766	54.3	3103
1 x 630 RM / 35	0.047	675	890	57.9	3664

CONTACT PERSON

Vojtěch Cuřín
Product Supervisor
+420 731 226 023
vojtech.curin@prakab.com

