



We Make Modern
Life Possible

FLEXICS® TRUCK TWIN FLYY

PVC/PVC twin battery cable for commercial
vehicles



TECHNICAL DATA

	Standard Acc. to ISO 6722-1 and ISO 14572 / temperature class A		Fire properties ISO 6722-1, ISO 14572, ISO 4141
	Test Voltage 3000 V / 50 Hz		Core identification Black and red
	Rated Voltage 60 V (U ₀ /U)		Temperature range Operating temperature: -40°C up to 85°C
	Bending radius (min.) 15 x Ø of cable		

DESIGN



- 1 Bare copper conductors, fine wires according to ISO 6722-1
- 2 Core insulation of special compound based on polyvinyl chloride (PVC)
- 3 Outer sheath of special compound based on polyvinyl chloride (PVC), colour: black (RAL 9005)

Number of cores x nominal cross-section (mm²)	Outer dimensions width x height (mm)	Cu-value (kg/km)	Total weight appr. (kg/km)
2 x 6	15.2 x 7.4	115.2	201
2 x 10	18.8 x 9	192	304
2 x 16	20.9 x 10	307.2	442
2 x 25	25.6 x 12.4	480	671
2 x 35	28 x 13.7	672	883
2 x 50	33 x 17	960	1261
2 x 70	35.1 x 16.8	1344	1799

CONTACT PERSON

Dipl. Ing. Peter Tomka

+421 37 6969631
peter.tomka@ics-cables.sk