



We Make Modern
Life Possible

FLEXICS® JET 400Hz 2X11Y

Single core ground power supply cable, with
control cores, tinned and halogen-free



TECHNICAL DATA



Test Voltage
4000 V / 50 Hz



Rated Voltage
0.6/1 kV (U₀/U)



Bending radius (min.)
6 x Ø of cable



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant
IEC 60754-1: halogen-free



Core identification
Grey (continuously numbered)



Temperature range
Operating temperature: -40°C up to 90°C

DESIGN



- 1 Tinned copper conductors, fine wires class 5 (control cores) and super fine wires class 6 (power cores) according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Control core with two layer (natural & grey color) insulation on polypropylene and polyurethane basis, continuously numbered
- 3 Designed number of control cores stranded together within copper conductor strand
- 4 Non-woven tape separation
- 5 Primary outer sheath of special compound based on cross-linked polymer (XLPE), colour: orange (RAL 2003)
- 6 Secondary outer sheath of special polyurethane (PUR), colour: yellow (RAL 1021)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Cu-value (kg/km)	Total weight appr. (kg/km)
1 x 50 + 4 x 1	17.6	519	682
1 x 70 + 4 x 1	20.2	711	904
1 x 70 + 6 x 1	20.8	730	932
1 x 120 + 4 x 1	24.5	1191	1445

CONTACT PERSON

Dipl. Ing. Peter Tomka

+421 37 6969631
 peter.tomka@ics-cables.sk

