


SAFETY CABLES

JE-H(St)H...Bd FE180/E30 red

halogen-free installation control cable with
insulation integrity and circuit integrity,
screened



TECHNICAL DATA



Standard
adapted to DIN VDE 0815



Certificate
VDE Germany



Test Voltage
core/core 500 V / 50 Hz
core/screen 2000 V / 50 Hz



Rated Voltage
max. 225 Vss



Bending radius (min.)
7,5 x Ø of cable



Fire properties
EN 60332-1-2: self-extinguishing
EN 60754-2: halogen-free, non-corrosive
combustion gases
EN 61034-2: low smoke emission
EN 60332-3-22: reduced flame propagation
IEC 60331-23: insulation integrity FE180
DIN 4102-12: circuit integrity E30-E90



Core identification
DIN VDE 0815



Temperature range
Laying temperature: min. -5°C
Operating temperature: -30°C up to 70°C

DESIGN



Copper conductor, round solid (RE)



Core insulation (silicone rubber), cores pair stranded,
marking with green thread



Inner covering (plastic tape)



Screen (plastic laminated aluminium tape with drain wire)



Sheath (halogen-free polymer compound, red)

Electrical Parameters

Loop resistance max	Ω/km	73.2
Mutual capacitance, max.	nF/km	144
Capacitance unbalance, max. k	pF/500m	400
Conductor diameter	mm	0.8
Insulation resistance, min. at 20 °C	M Ω/km	100
Mutual capacitance (approx. value), at 800 Hz	nF/km	120

Number of pairs x nominal diameter	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 2 x 0.8	8.1	86
4 x 2 x 0.8	11.3	140

CONTACT PERSON

Ing. Štěpán Laštůvka
 Product Supervisor
 +420 732 912 682
stepan.lastuvka@prakab.com

