


SAFETY CABLES

JE-H(St)H...Bd FE180/E30-E90

halogen-free installation control cable with
insulation integrity and circuit integrity,
screened, VDE Reg. Nr. 8553



TECHNICAL DATA



Standard
adapted to DIN VDE 0815



Certificate
VDE Germany



Test Voltage
core/core 500 V / 50 Hz
core/screen 2000 V / 50 Hz



Rated Voltage
max. 225 Vss



Bending radius (min.)
7,5 x Ø of cable



Fire properties
EN 60332-1-2: self-extinguishing
EN 60754-2: halogen-free, non-corrosive
combustion gases
EN 61034-2: low smoke emission
EN 60332-3-22: reduced flame propagation
IEC 60331-23: insulation integrity FE180
DIN 4102-12: circuit integrity E30-E90



Core identification
DIN VDE 0815



Temperature range
Laying temperature: min. -5°C
Operating temperature: -30°C up to 70°C

DESIGN



Copper conductor, round solid (RE)



Core insulation (silicone rubber), cores pair stranded,
marking with green thread



Inner covering (plastic tape)



Screen (plastic laminated aluminium tape with drain wire)



Sheath (halogen-free polymer compound, orange or red)

Electrical Parameters

Conductor diameter	mm	0.8
Loop resistance max.	Ω/km	73.2
Mutual capacitance (approx. value), at 800 Hz	nF/km	120
Mutual capacitance, max.	nF/km	144
Capacitance unbalance, max. k	pF/500m	400
Insulation resistance, min. at 20 °C	MΩ/km	100

Number of pairs x nominal diameter	Outer diameter appr. (mm)	Total weight appr. (kg/km)
1 x 2 x 0.8	7.5	69
2 x 2 x 0.8	8.2	89
4 x 2 x 0.8	11.3	142
8 x 2 x 0.8	14.0	230
12 x 2 x 0.8	16.4	314
16 x 2 x 0.8	18.8	412
20 x 2 x 0.8	20.5	493
32 x 2 x 0.8	25.4	752
40 x 2 x 0.8	27.9	908
52 x 2 x 0.8	31.0	1166



System / System Manufacturer	System identification	Classification	Range	Distance (a) /Width (b) / Load (g)	AbP number	Laying type No.
Normtrag	Rinne	E90	n x 2 x = 0.8	a ≤ 1200 mm b = 300 mm g ≤ 10 kg/m	P-MPA-E-09-016	2.2.14 – 2
Normtrag	Leiter	E60	n x 2 x = 0.8	a ≤ 1200 mm b = 400 mm g ≤ 20 kg/m	P-MPA-E-09-016	2.2.14 – 1
Normtrag	Abstandschele	E90	n x 2 x = 0.8	a ≤ 300 mm	P-MPA-E-09-016	2.2.14 – 3
Normtrag	Bügeschelle mit LW	E90	n x 2 x = 0.8	a ≤ 600 mm	P-MPA-E-09-016	2.2.14 – 4
OBO Bettermann	GRM 55/ + AW15/ (AWG15/)	E90	n x 2 x = 0.8	a ≤ 1500 mm b = 400 mm g ≤ 15 kg/m	P-MPA-E-23-003	5.1
OBO Bettermann	2056/M	E90	n x 2 x = 0.8	a ≤ 800 mm	P-MPA-E-23-003	8.1
OBO Bettermann	2034M	E90	n x 2 x = 0.8	a ≤ 500 mm	P-MPA-E-23-003	10.2
OBO Bettermann	RKSM 630 + AW55/31	E90	n x 2 x = 0.8	a ≤ 1500 mm b = 300 mm g ≤ 20 kg/m	P-MPA-E-23-001	1.1
OBO Bettermann	RKSM 640 + AW55/41	E90	n x 2 x = 0.8	a ≤ 1500 mm b = 400 mm g ≤ 20 kg/m	P-MPA-E-23-001	1.2
OBO Bettermann	FireBox T350ED 4-28 AD + 732 (decke)	E90	n x 2 x = 0.8		P-1036 DMT DO	XV
OBO Bettermann	FireBox T350ED 4-28 AD + 732 (decke)	E90	n x 2 x = 0.8		P-1036 DMT DO	XVI
OBO Bettermann	2031-M/30	E60	n x 2 x = 0.8	a ≤ 600 mm g ≤ 3 kg/m	P-MPA-E-23-003	6.2
OBO Bettermann	732/733	E60	n x 2 x = 0.8	a ≤ 800 mm	P-MPA-E-23-003	8.2
OBO Bettermann	RKSM 640 + AW55/41	E60	n x 2 x = 0.8	a ≤ 1550 mm b = 400 mm g ≤ 20 kg/m	P-1036 DMT DO	II
OBO Bettermann	2031-M/70	E30	n x 2 x = 0.8	a ≤ 800 mm g ≤ 6 kg/m	P-MPA-E-23-003	6.3
OBO Bettermann	2033M	E30	n x 2 x = 0.8	a ≤ 500 mm	P-MPA-E-23-003	10.1
OBO Bettermann	2031/M30	E30	n x 2 x = 0.8	a ≤ 500 mm g ≤ 2.5 kg/m	P-1016 DMT DO	XI
OBO Bettermann	RKSM 630 + AW55/31	E30	n x 2 x = 0.8	a ≤ 1550 mm b = 300 mm g ≤ 20 kg/m	P-1036 DMT DO	I
OBO Bettermann	RKSM 630 + AW55/31	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 300 mm g ≤ 20 kg/m	P-1036 DMT DO	XIII
OBO Bettermann	RKSM 640 + AW55/41	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 400 mm g ≤ 20 kg/m	P-1036 DMT DO	XIV
Niedax	SHS30 (wand)	E90	n x 2 x = 0.8	a ≤ 600 mm g ≤ 3 kg/m	P-MPA-E-09-016	2.2.16 – 4
Niedax	SHS30 (decke)	E90	n x 2 x = 0.8	a ≤ 600 mm g ≤ 3 kg/m	P-MPA-E-09-016	2.2.17 – 6
Niedax	Bügeschellen B	E60	n x 2 x = 0.8	a ≤ 800 mm	P-MPA-E-23-003	9.1
Niedax	Abstandschele SAS	E60	n x 2 x = 0.8	a ≤ 800 mm	P-MPA-E-23-003	9.2
Niedax	RLVC 60.400 S + KTAS400 (wand)	E60	n x 2 x = 0.8	a ≤ 1500 mm b = 400 mm g ≤ 30 kg/m	P-1036 DMT DO	XI
Niedax	RLVC 60.300 + KTAS300	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 300 mm g ≤ 20 kg/m	P-MPA-E-23-003	3.1



System / System Manufacturer	System identification	Classification	Range	Distance (a) /Width (b) / Load (g)	AbP number	Laying type No.
Niedax	SHS15	E30	n x 2 x = 0.8	a ≤ 600 mm g ≤ 3 kg/m	P-MPA-E-23-003	7.1
Niedax	SHS80	E30	n x 2 x = 0.8	a ≤ 800 mm g ≤ 6 kg/m	P-MPA-E-23-003	7.3
Niedax	LLK	E30	n x 2 x = 0.8	a ≤ 500 mm g ≤ 3 kg/m	P-MPA-E-23-003	12.1
Niedax	RLVC 60.400 S + KTA400	E30	n x 2 x 0.8	a ≤ 1500 mm b = 400 mm g ≤ 30 kg/m	P-1016 DMT DO	II
Niedax	RLVC 60.300 S + KTAS300	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 300 mm g ≤ 25 kg/m	P-1036 DMT DO	VII
Niedax	RLVC 60.400 S + KTAS400	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 400 mm g ≤ 30 kg/m	P-1036 DMT DO	VIII
Niedax	SHS30 (decke)	E30	n x 2 x = 0.8	a ≤ 600 mm g ≤ 3 kg/m	P-1036 DMT DO	IX
Niedax	SHS80 (wand)	E30	n x 2 x = 0.8	a ≤ 800 mm g ≤ 6 kg/m	P-1036 DMT DO	X
Niedax	RLVC 60.300 S + KTAS300 (wand)	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 300 mm g ≤ 25 kg/m	P-1036 DMT DO	XII
Niedax	MTC 54.050 + GTCB 50/100	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 50 mm g ≤ 5 kg/m	P-1036 DMT DO	XXII
Niedax	MTC 54.200 + KTAS200	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 200 mm g ≤ 15 kg/m	P-1036 DMT DO	XXI
Lanz	WSP-Multibahn 400x60 (decke)	E90	n x 2 x 0.8	a ≤ 1800 mm g ≤ 20 kg/m	P-1016 DMT DO	XIV
Lanz	G-Kanal 50x100	E30	n x 2 x 0.8	a ≤ 1500 mm g ≤ 10 kg/m	P-1016 DMT DO	IV
Lanz	WSP-Multibahn 400x60 (wand)	E30	n x 2 x 0.8	a ≤ 1800 mm g ≤ 20 kg/m	P-1016 DMT DO	XIII
PUK	RG 60-30S + KWMS 030F	E90	n x 2 x = 0.8	a ≤ 1550 mm b = 300 mm g ≤ 20 kg/m	P-1036 DMT DO	IV
PUK	RG 60-40S + KWMS 040F	E90	n x 2 x = 0.8	a ≤ 1550 mm b = 400 mm g ≤ 20 kg/m	P-1036 DMT DO	V
PUK	RG 60-40S + KWMS 040F (wand)	E90	n x 2 x = 0.8	a ≤ 1500 m b = 400 mm g ≤ 20 kg/m	P-1036 DMT DO	VI
PUK	LGG-BS 60-40-3S + KW 040F	E60	n x 2 x = 0.8	a ≤ 1200 mm b = 400 mm g ≤ 20 kg/m	P-1036 DMT DO	XVII
PUK	LGG-BS 60-40-3S + KW 040F	E60	n x 2 x = 0.8	a ≤ 1500 mm b = 400 mm g ≤ 20 kg/m	P-1036 DMT DO	XVIII
PUK	RG 60-30S + KWMS 030F	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 300 mm g ≤ 20 kg/m	P-1036 DMT DO	III
PUK	GI 30S + KWMS 030F	E30	n x 2 x = 0.8	a ≤ 1500 mm b = 300 mm g ≤ 15 kg/m	P-1036 DMT DO	XIX
PUK	SH QS 15	E30	n x 2 x = 0.8	a ≤ 500 mm g ≤ 1.5 kg/m	P-1036 DMT DO	XX
PohlCon	RG-BS 60-40E4 + DB-T 40EC	E90	≥ 2 x 2 x = 0.8	a ≤ 1500 mm b = 400 mm g ≤ 30 kg/m	P-1043 DMT DO	I



System / System Manufacturer	System identification	Classification	Range	Distance (a) /Width (b) / Load (g)	AbP number	Laying type No.
PohlCon	RG-BS 60-30E4 + DB-T 30EC	E90	$\approx 2 \times 2 \times \approx 0.8$	a $\leq$ 1500 mm b = 300 mm g $\leq$ 15 kg/m	P-1043 DMT DO	II
PohlCon	Bügeschelle AC + KHA 8	E90	$\approx 2 \times 2 \times \approx 0.8$	a $\leq$ 800 mm	P-1043 DMT DO	VII
PohlCon	Bügeschelle AC + KHA 7	E90	$\approx 2 \times 2 \times \approx 0.8$	a $\leq$ 750 mm	P-1043 DMT DO	IX

CONTACT PERSON

Ing. Štěpán Laštůvka
 Product Supervisor
 +420 732 912 682
stepan.lastuvka@prakab.com

