
We Make Modern
Life Possible.

CONDUCTORS

Copper wire braidings, flat




Bare copper wire braidings, flat

Our bare copper wire braidings / earthing straps are used for protective earthing within cabinets or for applying an additional shield around electrial connections in dry rooms without corrosive
environment.

TECHNICAL DATA

Standard
TS ICS 43-2020

DESIGN



1 Bare copper wire or stranded bare copper wire braiding (flat)

Copper wire braidings, flat

Bare copper wire braidings, flat

Single wire diameter (mm)	Conductor cross section (mm²)	Width of flatted conductor (mm)	Height of flatted conductor (mm)	Cu-value (kg/km)
0.07	6	8.5	0.9	58
0.07	10	11.5	1.2	96
0.07	16	15.2	1.4	154
0.07	20	16.8	1.7	192
0.07	25	19	1.9	240
0.07	35	21.5	2.4	336
0.1	10	11.2	1.3	96
0.1	16	15.5	1.5	154
0.1	25	20	2	240
0.1	35	24	2.2	336
0.1	50	28.5	2.8	480
0.2	25	22	1.6	240
0.2	35	24.5	2.4	336
0.2	50	31	2.7	480
0.2	70	35	3.8	672

Technical changes reserved. All figures are therefore without guarantee.



CONTACT PERSON

Dipl. Ing. Peter Tomka

+421 37 6969631
peter.tomka@ics-cables.sk