KONEKA

We Make Modern Life Possible.



INSULATED OVERHEADLINES

NFA2X

XLPE insulated bundled overhead line

Conductors are designed for outdoor distribution of electrical energy in suspended design.

TECHNICAL DATA

Standard
DIN VDE 0276-626 (HD 626)
ČSN 34 7614-4F
ČSN 34 7614-9F

Certificate
VDE Germany

Test Voltage
4 kV / 50 Hz

Rated Voltage
0.6/1 kV

Bending radius (min.)
18 x Ø of cable

Core identification
1, 2 resp.3 raised longitudinal ribs on the surface of the cores. The surface of the neutral conductor is smooth.

Temperature range
Laying temperature: min. -20°C
Operating temperature: -30°C up to 80°C
Conductor temperature: max. 80°C
Short circuit temperature: max. 130°C

DESIGN



1. Aluminium conductor with increased breaking load, round stranded compressed (RM)
2. Core insulation (XLPE black, UV-resistant); 2 or 4 cores of equal cross section are stranded together in left-hand lay, additionaly 1 or 2 cores of reduced cross section can be co-stranded

Number of cores x nominal cross-section [mm²]	Max. conductor resistance (Ω/km)	Min. breaking load of conductor strand (kN)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
1 x 16 RM*	1.91	2.5	81	8.0	75
2 x 16 RM*	1.9	2.5	81	15.6	150
4 x 16 RM*	1.91	2.5	81	18.8	290
1 x 25 RM	1.2	4	107	9.0	110
2 x 25 RM*	1.2	4	107	18.0	210
4 x 25 RM	1.2	4	107	21.2	430
1 x 35 RM	0.868	5.5	132	10.0	135
2 x 35 RM*	0.868	5.5	132	20.0	270
4 x 35 RM	0.868	5.5	132	24.1	555
1 x 50 RM	0.641	8	165	11.8	185
2 x 50 RM*	0.641	8	165	23.5	365
4 x 50 RM	0.641	8	165	27.8	750
4 x 50 x 25 RM/RM*	0.641 / 1.2	8	165	31.9	815
4 x 50 x 35 RM/RM*	0.641 / 0.868	8	165	31.9	845
1 x 70 RM	0.443	10.7	205	13.4	255
4 x 70 RM	0.443	10.7	205	31.8	1010
4 x 70 x 25 RM/RM*	0.443 / 1.2	10.7	205	36.0	1110
4 x 70 x 35 RM/RM	0.443 / 0.868	10.7	205	36.2	1150
4 x 70 + 2 x 35 RM/RM	0.443 / 0.868	10.7	205	40.1	1290
1 x 95 RM*	0.32	13.7	249	15.4	335
4 x 95 RM*	0.32	13.7	249	37.8	1340
4 x 95 x 25 RM/RM*	0.32 / 1.2	13.7	249	41.8	1440
4 x 95 x 35 RM/RM*	0.32 / 0.868	13.7	249	41.8	1470
4 x 95 + 2 x 25 RM/RM*	0.32 / 1.2	13.7	249	42.0	1550
1 x 120 RM*	0.253	18.6	286	17.0	410
4 x 120 RM*	0.253	18.6	286	40.5	1600
1 x 150 RM*	0.206	23.2	334	19.0	505

Technical changes reserved. All figures are therefore without guarantee.

EPD
INTERNATIONAL EPD SYSTEM

CONTACT PERSON

Jan Pietroň
Key Account Manager
+420 604 471 907
jan.pietron@koneka.cz

