We Make Modern Life Possible.

INDUSTRIAL CABLES

FLEXICS® CHAIN C

PVC/PVC drag chain cable, screened

Extremely flexible PVC/PVC control cable for transmission of instrumentation and control signals for machine building and plant construction purposes, especially for continuous moving machine parts, e.g. within C-tracks. FLEXICS® CHAIN C cables are designed for indoor applications when exposed to medium mechanical stress, especially when excellent EMC behavior is requested.



TECHNICAL DATA

Standard
Based on VDE 0285

Test Voltage
4000 V / 50 Hz

Rated Voltage
300/500 V (Uo/U)

Bending cycles
3 million

Bending radius (min.)
Fixed installation: 7.5 x Ø of cable
Flexible use: 10 x Ø of cable

Fire properties
EN 60332-1-2: self-extinguishing and flame retardant

Core identification
Black (continuously numbered), from 3 cores with green/yellow ground conductor

Temperature range
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



1. Bare copper conductors, super fine wires class 6 according to DIN EN 60228 / VDE 0295 / IEC 60228
2. Core insulation of special compound based on polyvinyl chloride (PVC)
3. Cores stranded in layers with short lay-lengths
4. Non-woven wrapping over each stranding layer
5. Inner sheath of special compound based on polyvinyl chloride (PVC)
6. Tinned copper wire braiding
7. Non-woven tape separation over braiding (optional)
8. Outer sheath of special compound based on polyvinyl chloride (PVC), colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 0.5	6.9	73
3 G 0.5	7.3	84
4 G 0.5	7.9	98
5 G 0.5	8.6	110
7 G 0.5	9.8	141
12 G 0.5	11.5	201
18 G 0.5	13.4	285
25 G 0.5	15.9	394
2 x 0.75	7.3	85
3 G 0.75	7.8	98
4 G 0.75	8.4	116
5 G 0.75	9.0	128
7 G 0.75	10.7	178
12 G 0.75	12.5	253
18 G 0.75	14.9	367
25 G 0.75	17.4	496
2 x 1	7.7	97
3 G 1	8.2	116
4 G 1	8.9	134
5 G 1	9.8	154
7 G 1	11.4	207
12 G 1	13.4	314
18 G 1	16.1	443
25 G 1	18.8	612
2 x 1.5	8.4	117
3 G 1.5	9.0	139
4 G 1.5	9.9	169
5 G 1.5	10.9	201
7 G 1.5	12.7	262
12 G 1.5	15.2	404
18 G 1.5	17.8	560
25 G 1.5	21.2	788
3 G 2.5	11.0	206
4 G 2.5	11.9	244
5 G 2.5	13.2	306
7 G 2.5	15.8	418
12 G 2.5	20.4	690
18 G 2.5	24.0	994
25 G 2.5	28.2	1420
4 G 4	13.7	360
5 G 4	15.3	430
7 G 4	20.0	670
4 G 6	16.1	514
7 G 6	23.0	862

Technical changes reserved. All figures are therefore without guarantee.



CONTACT PERSON

Natalia Dikovits
Sales
+43 (0) 1 70170-120
natalia.dikovits@skw.at