We Make Modern Life Possible.

INDUSTRIAL CABLES

FLEXICS® TRUCK TWIN FLYY



PVC/PVC twin battery cable for commercial vehicles

Flat twin battery PVC sheathed cables for usage in vehicles. Connection and control cable between the voltage source and electrical appliances, e.g. for tail lifts, etc.

TECHNICAL DATA

Standard
Acc. to ISO 6722-1 and ISO 14572 / temperature class A

Fire properties
ISO 6722-1, ISO 14572, ISO 4141

Test Voltage
3000 V / 50 Hz


Core identification
Black and red

Rated Voltage
60 V (Uo/U)

Temperature range
Operating temperature: -40°C up to 85°C

Bending radius (min.)
15 x Ø of cable

DESIGN



1. Bare copper conductors, fine wires according to ISO 6722-1
2. Core insulation of special compound based on polyvinyl chloride (PVC)
3. Outer sheath of special compound based on polyvinyl chloride (PVC), colour: black (RAL 9005)

Number of cores x nominal cross-section (mm²)	Outer dimensions width x height (mm)	Total weight appr. (kg/km)
2 x 6	15.2 x 7.4	201
2 x 10	18.8 x 9	304
2 x 16	20.9 x 10	442
2 x 25	25.6 x 12.4	671
2 x 35	28 x 13.7	883
2 x 50	33 x 17	1261
2 x 70	35.1 x 16.8	1799

Technical changes reserved. All figures are therefore without guarantee.



CONTACT PERSON

Natalia Dikovits
Sales
+43 (0) 1 70170-120
natalia.dikovits@skw.at