We Make Modern Life Possible.

INDUSTRIAL CABLES

FLEXICS® CHAIN 11 UL/c(UL)

UL recognized PVC/PUR drag chain cable, unscreened

Extremely flexible PVC/PUR control cable for transmission of instrumentation and control signals for machine building and plant construction purposes, especially for continuous moving machine parts, e.g. within C-tracks. FLEXICS® CHAIN 11 UL/c(UL) cables are designed for both indoor and outdoor applications when exposed to high mechanical stress. Resistant against a wide range of oils, greases, coolants and lubricants.



TECHNICAL DATA

Standard
Based on VDE 0285

Certificate
UL AWM Style 20234
CSA C22.2 No. 210-11, AWM

Test Voltage
4000 V / 50 Hz

Rated Voltage
300/500 V (Uo/U)
1000 V (UL/CSA)

Bending cycles
5 million

Bending radius (min.)
Fixed installation: 7.5 x Ø of cable
Flexible use: 10 x Ø of cable

Fire properties
EN 60332-1-2: self-extinguishing and flame retardant
UL: vertical flame test VW-1, cable flame test
CSA: FT1

Core identification
Black (continuously numbered), from 3 cores with green/yellow ground conductor

Temperature range
Fixed installation: -30°C up to 80°C
Flexible use: -5°C up to 70°C

DESIGN



1. Bare copper conductors, super fine wires class 6 according to DIN EN 60228 / VDE 0295 / IEC 60228
2. Core insulation of special compound based on polyvinyl chloride (PVC)
3. Cores stranded in layers with short lay-lengths
4. Non-woven wrapping over each stranding layer
5. Special polyurethane (PUR) outer sheath, colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 0.5	6.5	46
3 G 0.5	6.8	55
4 G 0.5	7.5	69
5 G 0.5	8.0	85
7 G 0.5	9.8	117
12 G 0.5	10.8	155
18 G 0.5	12.7	224
25 G 0.5	15.2	328
2 x 0.75	6.8	54
3 G 0.75	7.3	66
4 G 0.75	8.0	82
5 G 0.75	8.7	101
7 G 0.75	10.7	142
12 G 0.75	11.7	196
18 G 0.75	13.9	282
25 G 0.75	16.6	404
2 x 1	7.1	60
3 G 1	7.7	75
4 G 1	8.5	94
5 G 1	9.2	117
7 G 1	11.4	168
12 G 1	12.6	231
18 G 1	15.1	343
25 G 1	18.4	538
2 x 1.5	7.7	78
3 G 1.5	8.4	98
4 G 1.5	9.3	125
5 G 1.5	10.1	151
7 G 1.5	11.9	221
12 G 1.5	13.9	318
18 G 1.5	16.9	484
25 G 1.5	20.1	671
3 G 2.5	9.3	134
4 G 2.5	10.3	170
5 G 2.5	11.3	205
7 G 2.5	13.4	295
12 G 2.5	16.0	440
18 G 2.5	20.4	698
25 G 2.5	24.7	1045
3 G 4	10.9	190
4 G 4	12.1	247
5 G 4	13.5	312
7 G 4	18.6	452
3 G 6	13.0	288

Number of cores x nominal cross-section (mm²)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
4 G 6	14.2	363
7 G 6	19.8	622

Technical changes reserved. All figures are therefore without guarantee.



CONTACT PERSON

Natalia Dikovits
Sales
+43 (0) 1 70170-120
natalia.dikovits@skw.at